



INVICTUS

# MAXIMUS

CLICK PARQUET WITH CORK



## Specification

Description		Rigid core SPC with cork backing
Thickness	EN ISO 24346	6.00 mm
Wearlayer	EN ISO 24340	0.55 mm
Weight per sqm	EN ISO 23997	10.000 g/m <sup>2</sup>
Surface PUR coating		Scratchmaster® top layer
Locking System		Unilin's Unizip® click technology
Classification	EN ISO 10874	23 Domestic Heavy - 33 Commercial Heavy - 42 Industrial General

## Performance

Reaction to fire	EN 13501-1	Bfl-S1
Slip resistance	EN 13893	DS
Slip resistance (dynamic coefficient of friction)	DIN 51130	R10
Thermal resistance (R value)	EN 12664	0.049 (m <sup>2</sup> .K)/W
Thermal conductivity	EN 12664	0.124 (W/m.K)
Underfloor heating	EN ISO 12524	Yes, max. 27°C
Electrostatic performance (antistatic)	EN 1815	< 2 kV
Residual indentation	EN ISO 24343-1	<0.15 mm
Dimensional stability	EN ISO 23999	≤ 0.15%
Dimensional stability (curling)	EN ISO 23999	pass
Castor chair resistance	EN ISO 4918	pass, Type W
Colour fastness	EN ISO 105-B02	>6
Impact sound insulation	EN ISO 717-2 (ΔLw)	18dB
Chemical / Stain resistance	EN ISO 26987	pass
Abrasion resistance	EN ISO 660-1	class T
French VOC regulation	ISO 16000	A+
Indoor AIR quality	ISO 16000	Greenguard GOLD
Indoor AIR quality		Floorscore
Content of pentachlorophenol		PCP under detection limit
Formaldehyde emissions	EN ISO 717-1 (28 days test)	NA HCHO (has not been added)
Phthalate free		Yes, biobased
CE marking		EN 14041:2011

## Packaging

		Size plank / tile	Pieces / carton
Size and packaging wood cork backing	EN ISO 24342	145 x 743 mm (5,7"x29,25")	14 planks / carton = 1.509 m <sup>2</sup> (16.24 ft <sup>2</sup> ) / carton

## Warranty

Warranty	25 years Residential - 15 years Commercial
----------	--

The technical data is correct at the time of printing. 07/2022





INVICTUS

# MAXIMUS

CLICK PARQUET WITH CORK



## INVICTUS MAXIMUS CLICK 55 (SPC click) - LIGHT REFLECTION VALUE BS.8493:2008+A1:2010.

DESSIN	LRV
Highland Oak Classic	23.8
Highland Oak Roasted	15.3
Highland Oak Chocolate	11.5
Divine Oak Champagne	36.8
Divine Oak Cookie	25.6
Divine Oak Pure	43.1

## INVICTUS MAXIMUS (SPC) CLICK - SLIP RESISTANCE Pendulum test values - BS 7976-2

TYPE	DESIGN	DRY		WET	
		Lowest Test Value	Slip Risk Class	Lowest Test Value	Slip Risk Class
WOOD	DIVINE OAK	63	LOW	37	LOW
WOOD	HIGHLAND OAK	71	LOW	38	LOW

