



INVICTUS

MAXIMUS

CLICK PARQUET 55



Specification

Description		Rigid core SPC with click locking system
Thickness	EN ISO 24346	5.00 mm
Wearlayer	EN ISO 24340	0.55 mm
Weight per sqm	EN ISO 23997	9700 g/m ²
Surface PUR coating		Scratchmaster® top layer
Locking System		Unilin's Unizip® click technology
Classification	EN ISO 10874	23 Domestic Heavy - 33 Commercial Heavy

Performance

Reaction to fire	EN 13501-1	Bfl-S1
Slip resistance	EN 13893	DS
Slip resistance (dynamic coefficient of friction)	DIN 51130	R10
Thermal conductivity	EN 12664	0.165 (W/m.K)
Thermal resistance (R value)	EN 12664	0.031 (m ² .K)/W
Underfloor heating	EN ISO 12524	Yes, max. 27°C
Electrostatic performance (antistatic)	EN 1815	< 2 kV
Residual indentation	EN ISO 24343-1	<0.1 mm
Dimensional stability	EN ISO 23999	≤ 0.25%
Dimensional stability (curling)	EN ISO 23999	pass
Castor chair resistance	EN ISO 4918	≥ 25000 Cycles, no damage
Colour fastness	EN ISO 105-B02	>6
Impact sound insulation	EN ISO 717-2 (ΔLw)	8dB (ΔLw)
Chemical / Stain resistance	EN ISO 26987	pass
Abrasion resistance	EN ISO 660-1	class T
French VOC regulation	ISO 16000	A+
Indoor AIR quality	ISO 16000	Greenguard GOLD
Indoor AIR quality		Floorscore
Content of pentachlorophenol		PCP under detection limit
Formaldehyde emissions	EN ISO 717-1 (28 days test)	NA HCHO (has not been added)
Phthalate free		Yes, biobased
CE marking		EN 14041:2011

Packaging

		Size plank / tile	Pieces /carton
Size and packaging wood	EN ISO 24342	145x743 mm (5,71"x29,25")	14 planks/carton = 1.509 m ² (16.52 ft ²) / carton

Warranty

Warranty 25 years Residential - 15 years Commercial

The technical data is correct at the time of printing, v1 - 08/2021

