



INVICTUS

# PRIMUS

CLICK 30



## Specification

Description		Rigid core SPC
Thickness	EN ISO 24346	4.00 mm
Wearlayer	EN ISO 24340	0.30 mm
Weight per sqm	EN ISO 23997	ca. 7680 g/m <sup>2</sup>
Surface PUR coating		Scratchmaster® top layer
Classification	EN ISO 10874	23 Domestic Heavy - 31 Commercial Moderate

## Performance

Reaction to fire	EN 13501-1	Bfl-S1
Slip resistance	EN 13893	DS
Slip resistance (dynamic coefficient of friction)	DIN 51130	R10
Thermal resistance (R value)	EN 12664	0,04 (m <sup>2</sup> .K)/W
Underfloor heating	EN ISO 12524	Yes, max. 27°C
Electrostatic performance (antistatic)	EN 1815	< 2 kV
Residual indentation	EN ISO 24343-1	<0.1 mm
Dimensional stability	EN ISO 23999	≤ 0.15%
Dimensional stability (curling)	EN ISO 23999	pass
Castor chair resistance	EN ISO 4918	pass, Type W
Colour fastness	EN ISO 105-B02	>6
Impact sound insulation	EN ISO 717-2 (ΔLw)	18dB (ΔLw) (with FIRMO underlay)
Chemical / Stain resistance	EN ISO 26987	pass
Abrasion resistance	EN ISO 660-1	class T
French VOC regulation	ISO 16000	A+
Indoor AIR quality	ISO 16000	Greenguard GOLD
Indoor AIR quality		Floorscore
Content of pentachlorophenol		PCP under detection limit
Formaldehyde emissions	EN ISO 717-1 (28 days test)	NA HCHO (has not been added)
Phthalate free		Yes, biobased
CE marking		EN 14041:2011

## Packaging

		Size plank / tile	Pieces /carton
Size and packaging wood	EN ISO 24342	225x1500 mm (9"x59")	6 planks / carton = 2.025 m <sup>2</sup> / carton
Size and packaging stone	EN ISO 24342	450x907 mm (18"x36")	6 tiles / carton = 2.449 m <sup>2</sup> / carton

## Warranty

Warranty	20 years
----------	----------

The technical data is correct at the time of printing. v2 - 02/2021

