



INVICTUS

MAXIMUS

CLICK 55



Specification

Description	Rigid core SPC with sound insulating underlay attached	
Thickness	EN ISO 24346	6.00 mm
Wearlayer	EN ISO 24340	0.55 mm
Weight per sqm	EN ISO 23997	9530 g/m ²
Surface PUR coating	Scratchmaster® top layer	
Locking System	Unilin's Unipush® click technology	
Classification	EN ISO 10874	23 Domestic Heavy - 33 Commercial Heavy

Performance

Reaction to fire	EN 13501 -1	Bfl-S1
Slip resistance	EN 13893	DS
Slip resistance (dynamic coefficient of friction)	DIN 51130	R10
Thermal resistance (R value)	EN 12664	0.048 (m ² .K)/W
Underfloor heating	EN ISO 12524	Yes, max. 27°C
Electrostatic performance (antistatic)	EN 1815	< 2 kV
Residual indentation	EN ISO 24343-1	<0.1 mm
Dimensional stability	EN ISO 23999	≤ 0.15%
Dimensional stability (curling)	EN ISO 23999	pass
Castor chair resistance	EN ISO 4918	pass, Type W
Colour fastness	EN ISO 105-B02	>6
Impact sound insulation	EN ISO 717-2 (ΔLw)	18dB
Chemical / Stain resistance	EN ISO 26987	pass
Abrasion resistance	EN ISO 660-1	class T
French VOC regulation	ISO 16000	A+
Indoor AIR quality	ISO 16000	Greenguard GOLD
Indoor AIR quality		Floorscore
Content of pentachlorophenol		PCP under detection limit
Formaldehyde emissions	EN ISO 717-1 (28 days test)	NA HCHO (has not been added)
Phthalate free		Yes, biobased
CE marking		EN 14041:2011

Packaging

		Size plank / tile	Pieces / carton
Size and packaging wood	EN ISO 24342	178x1213 mm (7"x47.75")	8 planks / carton = 1.725 m ² (18.57 ft ²) / carton
Size and packaging stone	EN ISO 24342	298x603 mm (11.75"x23.75")	8 tiles / carton = 1.440 m ² (15.503 ft ²) / carton

Warranty

Warranty	25 years Residential - 15 years Commercial
----------	--

The technical data is correct at the time of printing. v2 - 08 / 2019

