



INVICTUS

MAXIMUS

DRYBACK 55



Specification

Thickness	EN ISO 24346	2.50 mm
Wearlayer	EN ISO 24340	0.55 mm
Weight per sqm	EN ISO 23997	4310 g/m ²
Surface PUR coating		Scratchmaster® top layer
Classification	EN ISO 10874	23 Domestic Heavy - 33 Commercial Heavy - 42 Industrial General

Performance

Reaction to fire	EN 13501-1	Bfl-S1
Slip resistance	EN 13893	DS
Slip resistance (dynamic coefficient of friction)	DIN 51130	R10
Thermal resistance (R value)	EN 12664	0.028 (m ² .K)/W
Underfloor heating	EN ISO 12524	Yes, max. 27°C
Electrostatic performance (antistatic)	EN 1815	< 2 kV
Residual indentation	EN ISO 24343-1	<0.1 mm
Dimensional stability	EN ISO 23999	≤ 0.25%
Dimensional stability (curling)	EN ISO 23999	pass
Castor chair resistance	EN ISO 4918	pass, Type W
Colour fastness	EN ISO 105-B02	>6
Impact sound insulation	EN ISO 717-2 (ΔLw)	3dB
Chemical / Stain resistance	EN ISO 26987	pass
Abrasion resistance	EN ISO 660-1	class T
Content of pentachlorophenol		PCP under detection limit
Formaldehyde emissions	EN ISO 717-1 (28 days test)	NA HCHO (has not been added)
CE marking		EN 14041:2011

Packaging

		Size plank / tile	Pieces / carton
Size and packaging wood	EN ISO 24342	178x1219 mm (7"x48")	15 planks / carton = 3.25 m ² (35 ft ²) / carton
Size and packaging wood XL plank	EN ISO 24342	229x1517 mm (9"x59.72")	10 planks / carton = 3.47 m ² (37.33 ft ²) / carton
Size and packaging wood parquet	EN ISO 24342	102x406 mm (4"x16")	34 planks / carton = 1.40 m ² (15.11 ft ²) / carton
Size and packaging stone	EN ISO 24342	305x610 mm (12"x24")	18 tiles / carton = 3.34 m ² (36 ft ²) / carton
Size and packaging stone	EN ISO 24342	457x457 mm (18"x18")	16 tiles / carton = 3.34 m ² (36 ft ²) / carton
Size and packaging stone	EN ISO 24342	500x500 mm (19.69"x19.69")	14 tiles / carton = 3.50 m ² (37.67 ft ²) / carton
Size and packaging stone	EN ISO 24342	229x229 mm (9"x9")	40 tiles / carton = 2.09 m ² (22.50 ft ²) / carton

Warranty

Warranty

25 years Residential / 15 years Commercial

The technical data is correct at the time of printing. v1 - 06/2019

